

# WELCOTE 198 - PT

Skimcoating, Rendering & Levelling  
for 1mm to 4mm Thick (Superfine)

## *DESCRIPTION:*

**WELCOTE 198-PT** (Superfine) is a specially developed skim coating that can be applied from 1mm to 4mm thick. It gives a better and higher quality surface finishing when compared to normal finishes. It can also be used for covering up pin holes and surface unevenness.

**WELCOTE 198-PT** (Superfine) can be used on its own or in conjunction with **WELCOTE BASE**, the system will yield a highly superior quality plastered surface finishing.

## *BENEFITS:*

Improve durability  
Saves time and costs  
Solves aesthetic appearance due to cracked plasters  
Gives a better surface finishing  
Easy to use

## *TYPICAL APPLICATION:*

Bare concrete surfaces  
Hollow block surfaces  
Lightweight concrete surfaces  
Any plastered surfaces



SKIMCOATING

## TECHNICAL DATA:

Characteristic	Results
Colour	Grey: White
Workability	Approx 4 hours
CompleteDrying	About 24 hours 3
Bulk Density	Approx 1250 kg/cm
Maximum Grain Size	0.2 mm
Adhesion to concrete	s
@ 7 days	Approx. 1.2 N/mms
@ 28 days	Approx. 1.2 N/mm
Packaging	20 kgs./bag

## PACKAGING:

WELTCOTE 198-PT (Superfine) is packed in heavy duty 20 kg bags.

DISCLAIMER: The information given in this data sheet is based on years of experience and is correct to the best of our knowledge. However since the use of our product is in accordance with the instruction given, and their success in application is dependent on a number of factors, we can only be responsible for the quality of our product at the time of dispatch. Should any doubt arise about specification or application, do contact your service provider immediately.