

# WELBOND 338

EPOXY GROUT  
CEMENT GREY

## **DESCRIPTION:**

**WELBOND 338** is a 100% solid two-component Epoxy Coating formulated, high-grade resins and curing agents specially for flooring application. It is lead free and non-toxic when fully cured. It hardens to an abrasive resistant coating, with high adhesive strength on properly prepared substrates such as concrete and steel. **WELBOND 338** epoxy grout cement gray is water-permeable and has excellent resistant to oil, solvents,alkalis and most dilute acids.

## **USES:**

Ideal for floor topping of new and existing floor and pavements.Recommended for installation of non-skid coatings both indoor and outdoor.For patching of deteriorated flooring. High performance coating system.

## **SURFACE PREPARATION:**

As coating

\*Surface to be coated must be dry and free of oil, dirt, rust and loose particles and other contaminants.

Oil must be completely removed. It is recommended that steel surfaces be sandblasted to bare metal, concrete should be neutralized or acid – etched and washed thoroughly.

As Grouting

\*Preparation will be the same as WELBOND 358

EPOXY GROUT CEMENT

**PROPERTIES:**

Compressive Strength	
24 hrs.	7000-8000 psi
Curing Time	24 hrs./normal condition
Pot Life	20-30 minutes
Binder/Filler ratio	
1:2	Flowing
1:3	Mastic

**PACKAGING:**

1 GAL PER SET